

# SAFETY DATA SHEET

In accordance with 1907/2006 annex II 2015/830 and 1272/2008

(All references to EU regulations and directives are abbreviated into only the numeric term)

Issued 2018-11-12

Replaces issued SDS 2016-11-30

Version number 2.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name Sievert Propangas

Article number 200019, 200060, 201219

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Propellants

### 1.3. Details of the supplier of the safety data sheet

Company Sievert AB  
Box 1366  
17126 SOLNA  
Sweden  
Telephone +46 (0)8-629 22 00  
E-mail info@sievert.se

### 1.4. Emergency telephone number

Acute cases: Call 112, request poison information.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Extremely flammable gas (Category 1), H220

Compressed gas, H280

### 2.2. Label elements

Hazard pictogram



Signal word Danger

Hazard statements

H220 Extremely flammable gas

H280 Contains gas under pressure; may explode if heated

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely

P381 In case of leakage, eliminate all ignition sources

P410+P403 Protect from sunlight. Store in a well-ventilated place

### 2.3. Other hazards

This product does not contain any substances that are assessed to be a PBT or a vPvB

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Note that the table shows known hazards of the ingredients in pure form. These hazards are reduced or eliminated when mixed or diluted, see Section 16d.

Constituent	Classification	Concentration
<b>PROPANE</b>		
CAS No: 74-98-6 EC No: 200-827-9 Index No: 601-003-00-5 REACH: 01-2119486944-21	Flam Gas 1, Press Gas <i>P</i> ; H220, H280	>95 %
<b>ETHANE</b>		
CAS No: 74-84-0 EC No: 200-814-8 Index No: 601-002-00-X	Flam Gas 1A, Press Gas <i>P</i> ; H220, H280	<5 %
<b>BUTANE</b>		
CAS No: 106-97-8 EC No: 203-448-7 Index No: 601-004-00-0 REACH: 01-2119474691-32	Flam Gas 1, Press Gas <i>P</i> ; H220, H280	<5 %
<b>ETANETHIOL</b>		
CAS No: 75-08-1 EC No: 200-837-3 Index No: 016-022-00-9	Flam Liq 2, Acute Tox 4 <i>vapour</i> , Aquatic Acute 1, Aquatic Chronic 1; <i>M = 1</i> ; H225, H332, H400, H410	<0.005 %

Explanations to the classification and labelling of the ingredients are given in Section 16e. Official abbreviations are printed in normal font. Text in italics are specifications and/or complements used in the calculation of the classification of this mixture, see Section 16b.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Upon breathing in

Allow the injured person to rest in a warm place with fresh air, if symptoms persist seek medical attention.

#### Upon eye contact

Remove contact lenses immediately if possible.

Rinse the eye for several minutes with lukewarm water. If irritation persists call a doctor/ophthalmologist.

#### Upon skin contact

Remove contaminated clothes.

Heat the exposed body part in lukewarm water if cold injury occurs. Do NOT use warm water.

In case of major frost injuries, please contact your doctor.

#### Upon ingestion

If symptoms persist contact a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

#### Upon skin contact

Contact with rapidly expanding gas may cause frostbite.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

#### Recommended extinguishing agents

Extinguish with carbon dioxide, sand or powder.

#### Unsuitable extinguishing agents

Should not be extinguished with water.

### 5.2. Special hazards arising from the substance or mixture

Flammable gas.

In case of fire, high pressure may build up causing the packaging to explode.

Gases detrimental to health (carbon monoxide and carbon dioxide) can be spread in case of fire.

The gas forms an explosive mixture with air.

### 5.3. Advice for fire-fighters

In case of fire use a respirator mask.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Do not inhale the gas.

Note, risk of ignition and explosion.

Use recommended safety equipment, see section 8.

Upon small spillage < 5 kg. Evacuate the area and ventilate fumes.

Switch off equipment which has an exposed flame, glows, or has a heat source of some other kind.

Note, risk for formation of sparks due to static electricity. Do not remove clothing in a room where spillage has occurred.

Chemical protection suits should be worn for all salvage and decontamination work.

### 6.2. Environmental precautions

Avoid emissions into soil, water or air.

### 6.3. Methods and material for containment and cleaning up

Evacuate the area and ventilate fumes. Note, risk for explosion.

Do not use water or cleaning agents containing water.

### 6.4. Reference to other sections

See section 7, 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Handle in premises with good ventilation.

Do not inhale fumes and avoid contact with skin and eyes.

Store this product separately from food items and keep it out of the reach of children and pets.

Do not eat, drink or smoke in premises where this product is handled.

Open fires, hot objects, spark formation, or other sources of ignition, are not allowed in the premises where this product is handled. Prevent build up of static electricity by utilising a semi-conducting floor and shoe soles and keep humidity above 50%.

### 7.2. Conditions for safe storage, including any incompatibilities

The product should be stored in a manner which prevents hazards to health and the environment. Avoid exposure to humans and animals and do not discharge the product in a sensitive environment.

Store in a well-ventilated space.

Store in a dry place not above normal room temperature.

Contact with the liquid product can cause injuries from hypothermia.

Store tightly, in original packaging.

Avoid open fire, hot items, sparks or other ignition sources.

### 7.3. Specific end uses

See identified uses in Section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. National limit values

##### BUTANE

##### United Kingdoms (EH40/2005)

Time-weighted-average exposure limit (TWA) 600 ppm / 1450 mg/m<sup>3</sup>

Short term exposure limit (STEL) 750 ppm / 1810 mg/m<sup>3</sup>

##### ETANETHIOL

##### United Kingdoms (EH40/2005)

Time-weighted-average exposure limit (TWA) 0.5 ppm / 1.3 mg/m<sup>3</sup>

Short term exposure limit (STEL) 2 ppm / 5.2 mg/m<sup>3</sup>

##### DNEL

No data available.

##### PNEC

No data available.

### 8.2. Exposure controls

In terms of minimizing risks, attention must be paid to the physical hazards (see Sections 2 and 10) of this product according to EU directives 89/391 and 98/24 and national occupational legislation.

#### 8.2.1. Appropriate engineering controls

Handle in premises with good ventilation.

#### Eye/face protection

Not relevant.

#### Skin protection

Protective gloves are normally not needed due to the properties of this product, but may be necessary for other reasons, e.g. mechanical risks, temperature conditions or microbiological risks. Very sensitive persons can use gloves labelled "Low Chemical resistant" or "Waterproof" or with the pictogram indicated here.

#### Respiratory protection

A respiratory mask may be required.

#### 8.2.3. Environmental exposure controls

For limitation of environmental exposure, see Section 12.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

a) Appearance	Form: Liquefied gas. Colour: colourless.
b) Odour	Distinctive and unpleasant if odorized, otherwise odorless
c) Odour threshold	Not indicated
d) pH	Not indicated
e) Melting point/freezing point	Not indicated
f) Initial boiling point and boiling range	≈-45 °C
g) Flash point	-104 °C
h) Evaporation rate	Not indicated
i) Flammability (solid, gas)	Not applicable
j) Upper/lower flammability or explosive limits	Lower explosion limit 2.2% Upper explosion limit 10%
k) Vapour pressure	900 kPa (20 °C)
l) Vapour density	Not indicated
m) Relative density	0.5 g/cm <sup>3</sup> (20°C)
n) Solubility	Solubility in water: Very sparsely soluble(<0.1%)
o) Partition coefficient: n-octanol/water	Not applicable
p) Auto-ignition temperature	450 °C
q) Decomposition temperature	Not indicated
r) Viscosity	Not indicated
s) Explosive properties	Not applicable
t) Oxidising properties	Not applicable

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product contains no substances which can lead to hazardous reactions at normal use.

### 10.2. Chemical stability

The product is stable at normal storage and handling conditions.

### 10.3. Possibility of hazardous reactions

The gas forms an explosive mixture with air.

### 10.4. Conditions to avoid

Avoid heat, sparks and open flames.

### 10.5. Incompatible materials

Avoid contact with oxidizers.

### 10.6. Hazardous decomposition products

None under normal conditions.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

This product's main risk is its flammability.

Risk of frostbites.

### Acute toxicity

Not classified as an acutely toxic substance.

The product is not classified as harmful to health.

### PROPANE

LC50 rat 4h: 658 mg/L Inhalation

### BUTANE

LC50 rat 4h: 658 mg/L Inhalation

### Skin corrosion/irritation

The criteria for classification cannot be considered fulfilled based on available data.

### Serious eye damage/irritation

The criteria for classification cannot be considered fulfilled based on available data.

**Respiratory or skin sensitisation**

The criteria for classification cannot be considered fulfilled based on available data.

**Germ cell mutagenicity**

The criteria for classification cannot be considered fulfilled based on available data.

**Carcinogenicity**

The criteria for classification cannot be considered fulfilled based on available data.

**Reproductive toxicity**

The criteria for classification cannot be considered fulfilled based on available data.

**STOT-single exposure**

At high concentrations there is an anaesthetic or narcotic effect.

Prolonged inhalation can cause loss of consciousness and/or death.

The criteria for classification cannot be considered fulfilled based on available data.

**STOT-repeated exposure**

The criteria for classification cannot be considered fulfilled based on available data.

**Aspiration hazard**

The criteria for classification cannot be considered fulfilled based on available data.

## SECTION 12: Ecological information

**12.1. Toxicity**

The product is not classified as an environmental hazard according to current regulations, but it does contain environmentally hazardous substances in quantities below the labelling limit.

**PROPANE**

LC50 Freshwater water flea (*Daphnia magna*) 48h: 16.3 mg/L

LC50 Fish 96h: 16.1 mg/L

IC50 Algae 72h: 11.3 mg/L

**12.2. Persistence and degradability**

The product degrades in the natural environment.

**12.3. Bioaccumulative potential**

Neither this product, nor its contents, accumulates in nature.

**12.4. Mobility in soil**

No information about mobility in the nature exists but there is no reason to suppose the product to be ecologically harmful because of this.

**12.5. Results of PBT and vPvB assessment**

This product does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6. Other adverse effects**

No known effects or hazards.

## SECTION 13: Disposal considerations

**13.1. Waste treatment methods****Waste handling of the product**

Product as well as packaging must be disposed of as hazardous waste.

This product is not usually recycled.

Containers must not be perforated or burned.

Observe local regulations.

See also national waste regulations.

**Classification according to 2008/98**

Recommended LoW-code: 16 05 05 Gases in pressure containers other than those mentioned in 16 05 04

## SECTION 14: Transport information

Where not otherwise stated the information applies to all of the UN Model Regulations, i.e. ADR (road), RID (railway), ADN (inland waterways), IMDG (sea), and ICAO (IATA) (air).

**14.1. UN number**

1965

**14.2. UN proper shipping name**

HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S. (PROPANE)

### 14.3. Transport hazard class(es)

#### Class

2: Gases

#### Classification code (ADR/RID)

2F: Liquefied gas: flammable

#### Subsidiary risk (IMDG)

No subsidiary risk according to IMDG

#### Labels



### 14.4. Packing group

Not applicable

### 14.5. Environmental hazards

Not applicable

### 14.6. Special precautions for user

#### Tunnel restrictions

Tunnel category: B/D

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable

### 14.8 Other transport information

Transport category: 2; Highest total quantity per transported unit 333 kg or liters

Stowage category E (IMDG)

Emergency Schedule (EmS) for FIRE (IMDG) F-D

Emergency Schedule (EmS) for SPILLAGE (IMDG) S-U

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Not indicated.

### 15.2. Chemical safety assessment

Chemical safety report according to 1907/2006 Annex I is not required for this product.

## SECTION 16: Other information

### 16a. Indication of where changes have been made to the previous version of the safety data sheet

#### Revisions of this document

Earlier versions

2016-11-30 Changes in section(s) 3, 4, 6, 7, 10, 11, 12, 13.

### 16b. Legend to abbreviations and acronyms used in the safety data sheet

#### Full texts for Hazard Class and Category Code mentioned in section 3

Flam Gas 1	Extremely flammable gas (Category 1)
Press Gas <i>P</i>	Compressed gas
Flam Gas 1A	Extremely flammable gas, ignitable < 13 % (Category 1A)
Flam Liq 2	Flammable liquids (Category 2)
Acute Tox 4 <i>vapour</i>	Acute toxicity (Category 4 vapours)
Aquatic Acute 1	Very toxic to aquatic life (Category Acute 1)
Aquatic Chronic 1; <i>M = 1</i>	Very toxic to aquatic life with long lasting effects to aquatic environments (Category Chronic 1)

#### Explanations of the abbreviations in Section 14

ADR European Agreement concerning the International Transport of Dangerous Goods by Road

RID Regulations concerning the International Transport of Dangerous Goods by Rail

IMDG International Maritime Dangerous Goods Code

ICAO International Civil Aviation Organization (ICAO, 999 University Street, Montreal, Quebec H3C 5H7, Canada)

IATA The International Air Transport Association

Tunnel restriction code: B/D; Transport in tanks: Passage not permitted through tunnels of category B, C, D and E. Other transport: Passage not permitted through tunnels of category D and E

Transport category: 2; Highest total quantity per transported unit 333 kg or liters

### 16c. Key literature references and sources for data

#### Sources for data

Primary data for the calculation of the hazards has preferentially been taken from the official European classification list, 1272/2008 Annex I, as updated to 2018-11-12.

Where such data was not available, alternative documentation used to establish the official classification was used, e.g. IUCLID (International Uniform Chemical Information Database). As a second alternative, information was used from reputable international chemical industries, and as a third alternative other available information was used, e.g. material safety data sheets from other suppliers or information from non-profit associations, where reliability of the source was assessed by expert opinion. If, in spite of this, reliable information could not be sourced, the hazards were assessed by expert opinions based on the known hazards of similar substances, and according to the principles in 1907/2006 and 1272/2008.



### Full texts for Regulations mentioned in this Safety Data Sheet

- 1907/2006 REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC
- 2015/830 COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- 1272/2008 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
- EH40/2005 EH40/2005 Workplace exposure limits
- 89/391 COUNCIL DIRECTIVE (89/391/EEC of 12 June 1989 on the introduction of measures to encourage improvements in the safety and health of workers at work
- 98/24 COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)
- 2008/98 DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 19 November 2008 on waste and repealing certain Directives
- 1907/2006 REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

### 16d. Methods of evaluating information referred to in 1272/2008 Article 9 which was used for the purpose of classification

Hazard calculation for this mixture has been performed as a cumulative assessment with the aid of expert assessments in accordance with 1272/2008 Annex I, where all available information which may be significant to establishing the hazards of the mixture was assessed together, and in accordance with 1907/2006 Annex XI.

### 16e. List of relevant hazard statements and/or precautionary statements

#### Full texts for hazard statements mentioned in section 3

- H220 Extremely flammable gas
- H280 Contains gas under pressure; may explode if heated
- H225 Highly flammable liquid and vapour
- H332 Harmful if inhaled
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects

### 16f. Advice on any training appropriate for workers to ensure protection of human health and the environment

#### Warning for misuse

This product can cause injuries if not used properly. The manufacturer, the distributor or the supplier are not responsible for adverse effects if the product is not handled in accordance with its intended use.

#### Other relevant information

Not indicated

#### Editorial information



This material safety data sheet has been prepared and checked by KemRisk®, KemRisk Sweden AB, Platensgatan 8, SE-582 20 Linköping, Sweden, [www.kemrisk.se](http://www.kemrisk.se)